

Transparent protective coatings

Protecting cement floors and walls with a good quality Cemcrete sealer is crucial and not only makes the surface easier to clean, it offers other benefits as well, such as enriching the colour intensity of the overlay, blocking the penetration of stains, and improving water repellency and abrasion resistance.

COLOUR HARDENER SEALER - SOLVENT-BASED ACRYLIC SEALER

| Finish | Gloss or matt finish |
|-----------|--|
| Packaging | 1, 5 & 25 litre containers |
| Coverage | Approximately 4 - 8m² per litre per coat. Coverage depends on the porosity of the substrate The first coat will penetrate and then the subsequent coats should require less sealer |
| Curing | Initial set: 2 to 3 hours depending on weather Final cure: 7 days |

CRETESEAL WATER-BASED - POLYURETHANE ACRYLIC WATER-BASED SEALER

| Finish | Satin sheen |
|-----------|--|
| Packaging | 1, 5 & 20 litre containers |
| Coverage | Approximately 8 - 10m²/litre for the first coat and 10 - 12m²/litre for subsequent coats Although the spreading rate will vary with porosity and type of substrate |
| Curing | Initial set: 6 to 8 hours Final cure: 7 to 10 days |

CRETESEAL SOLVENT-BASED - POLYURETHANE SOLVENT-BASED SEALER

| Finish | Gloss |
|-----------|---|
| Packaging | 1 & 5 litre containers |
| Coverage | For uncoated new surfaces work on 10 - 12m²/litre for the first coat and 12 - 14m²/litre for subsequent coats Although the spreading rate will vary with porosity and type of substrate |
| Curing | Initial set: 12 hours Final cure: 7 to 10 days |

MULITPURPOSE SEALER WATER-BASED - NON-YELLOWING CLEAR POLYMER SEALER

| Finish | Gloss or super matt |
|-----------|--|
| Packaging | 1, 5 & 20 litre containers |
| Coverage | Approximately 5 - 6m² per litre per coat |
| Curing | Initial set: 4 hours Final cure: 3 days |

SILICONSEAL - PENETRATIVE SEALER (WET-ON-WET APPLICATION)

| Finish | No colour or sheen effect on surface |
|-----------|--|
| Packaging | 1, 5 & 25 litre containers |
| Coverage | Face bricks - 6m²/litre Porous bricks - 3m²/litre Concrete - 4m²/litre |
| Curing | Initial set: Solvents evaporate after 2 days plus Final cure: 22 days |

SLIP RESISTANT ADDITIVE - WHITE FINE GRANULES

| Finish | No colour or sheen effect on surface |
|-----------|--------------------------------------|
| Packaging | 90g's (enough for 5 litre) |